







Vergleich DTX-1800 / DSX-600 / DSX-5000 / DSX-8000

	DTX-1800 CableAnalyzer™ 	DSX-600 CableAnalyzer™ 	DSX-5000 CableAnalyzer™ 	DSX-8000 CableAnalyzer™ 
Dauer des Autotests	22 s Klasse E _A /Cat 6A 18 s Klasse E/Cat 6	10 s Klasse E _A /Cat 6A 9 s Klasse E/Cat 6	10 s Klasse E _A /Cat 6A 9 s Klasse E/Cat 6	16 s Cat 8 / Klasse I/II 8 s Klasse E _A /Cat 6A 7 s Klasse E/Cat 6
Erweiterte Fehlerinformation	Nein	Limitiert – (HDTDR & HDTDx)	Ja	Ja
Touch screen	Nein	Ja	Ja	Ja
ProjX™ Management System	Nein	Ja	Ja	Ja
Maximale Frequenz	500 MHz	500 MHz	1 GHz	2 GHz
PoE-Widerstand-Unsymmetrie	Nein	Nein	Ja	Ja
Überprüfen der Kabelschirmung	Nein	Ja	Ja	Ja
Patchkabel-Adapter	Opt.	Nein	Opt.	Opt.
Glasfaser – OLTS, OTDR, Insp.	Opt.	Nein	Opt.	Opt.
Interner Speicher	≈ 250 Cat 6 mit Grafik	≈ 12,000 Cat 6A mit Grafik	≈ 12,000 Cat 6A mit Grafik	≈ 12,000 Cat 6A mit Grafik
Unterstützung LinkWare Live SaaS	Nein	Ja	Ja	Ja
Unterstützung LinkWare PC	Ja	Ja	Ja	Ja